

DECLARATION OF PERFORMANCE

according to Regulation (EC) № 305/2011 of the European Parliament

DoP-CPR-BG-200P-210

1. *Unique identification code of the product type:*

**webertherm into HP
Load-bearing render**

2. *Intended use or uses of the construction product in accordance with the relevant harmonized technical specification as provided by the manufacturer:*

Load-bearing cement render for internal and external use, part of ETIC system webertherm Robusto.

3. *Name, registered trade name or registered trade mark and contact address of the manufacturer in accordance with Article 11, paragraph 5:*

**Saint-Gobain Bulgaria Ltd.
Industrial zone, 13 Imperator Konstantin Veliki str
2230 Kostinbrod, Bulgaria
Tel.: +359 2 400 37 00; Fax: +359 2 400 37 05
e-mail: office@weber.bg; web: www.bg.weber**

4. *Where applicable, the name and contact address of the authorized representative whose mandate covers the tasks referred to in Article 12, paragraph 2:*

Not applicable

5. *System or systems of assessment and verification of constancy of performance of construction product as set out in Annex V:*

The product has been evaluated according to System 4

6. *In the event of a declaration of performance concerning a construction product covered by a harmonized standard:*

Corresponds to standard EN 998-1:2016

The correspondence has been assessed by NISI EOOD - NB 2032 and issued initial product type test report № 1062/01.11.2017.

The product to which this declaration relates is manufactured under the conditions of a production control system put in place and maintained by the manufacturer.

7. *In the event of a declaration of performance concerning a construction product for which it was issued European Technical Assessment:*

Not applicable

8. *Declared performance*

Essential characteristics	Indicators of performance	Technical specification
Reaction to fire	A1	EN 998-1:2016
Water absorption	W2	
Resistance to water diffusion	$\mu < 20$	
Thermal conductivity	$\lambda = 0,40 \text{ W/mK}$	
Cohesion strength with concrete after 28 days	$\geq 0,7 \text{ N/mm}^2$	
Cohesion strength with EPS after 28 days	$\geq 0,2 \text{ N/mm}^2$	
Dangerous substances	NPD	

9. *Performance of the product referred to in paragraphs 1 and 2 correspond to the declared performance in point 8. This Declaration of Performance is issued under the sole responsibility of the manufacturer specified in paragraph 3.*

Signed for and on behalf of the manufacturer:

Ivan Rusev
COO, Saint-Gobain Bulgaria EOOD

Kostinbrod, 13.03.2023

