

Combined Veil and Mesh Joint Tape for Plasterboard FibaFuse® Double Strong

- Exceptional crack resistance
- Versatile application options using automatic drywall taping tools or hand tools
- No blisters or bubbles thanks to porous design





HOW TO APPLY FibaFuse® Double Strong?

1. Cover the joint with a thin coat of plaster (5–10 cm wide).
2. Apply the FibaFuse® tape directly onto joints mesh side facing the drywall.
3. Cover the fabric completely with a second thin coat of plaster.
4. To finish, cover with a further coat of plaster (15–20 cm wide).



FibaFuse® Double Strong is an innovative drywall tape combining nonwoven structure of classic FibaFuse® tape with additional reinforcement mesh layer resulting in extraordinary crack resistance. The tape is specially designed to be applicable with automatic drywall taping tools or simply by hand. Its porous design allows compound to flow through the tape and adhere neatly to the wall thus eliminating the risk of blisters or bubbles.

OTHER BENEFITS INCLUDE

- Versatile application options
- Ideal for high strength plasterboards like Habito® H
- Perfect for tapered as well as butt-end joints
- Easy repair of dry spots
- Works with any compound
- Easy to cut

USES

- Drywall joints
- Drywall finishing
- Crack repair

PACKAGING

roll	m ² / roll	rolls / box	rolls (boxes) / pallet
50 mm × 75 m	3,75	12	432 (36)

SAINT-GOBAIN

SAINT-GOBAIN ADFORS CZ s.r.o.
 Sokolovská 106
 570 01 Litomyšl • Czech Republic
 Tel.: + 420 461 651 111
 adfors.cpe@saint-gobain.com
 www.adfors.com



www.adfors.com