

## Rigips STANDARD CEE Jointfiller



### Product Description

STANDARD CEE is a fine gypsum filler for plasterboards, handling with adhesion tape.

Components: fine gypsum, additives and fillers for optimal handling.

### Advantages

STANDARD CEE is easy and smooth to apply, with low shrinkage and easy to sand. It is an inexpensive opportunity for filling joints.

### Application

For filling of joints and connections of plasterboards with Rigips joint tape. It is also used for smoothing of plasterboard surfaces till Q2.

### Site Conditions

Air-, material and background temperature have to be above +5°C.

The background has to be solid, clean, dust free and dry.

### Handling

Add approximately 1,4 kg STANDARD CEE into 1 litre of clean water and leave to stand for around 5 minutes. Then mix either by hand or with an electric drill with mud

paddle (low speed) till the mixture is lump-free. After the stirring process do not add further material. (lumps)

### On plasterboards:

Q1: Fill the joints and remove excessive material from surface. Bed Rigips paper tape into the joint and cover it with additional material.  
Q2: If necessary remove excessive material from joints. Once material set, cover the existing joint with additional material. This is necessary as long as any transitions exist. Once the material has dried, sand it if necessary.

As stiffened material should not be used or dissolved in water, otherwise cracks can occur.

Do not mix with other materials. Clean only with clean water.

### Quality Standard

Q1 – Q2

### EN-Classification

3B – EN 13963 – A1– NPD

### Product Data

<b>Mixing ratio</b>	app. 1,4 kg / 1 L water
<b>Working-time</b>	app. 40 min.
<b>Consumption</b>	<u>Joint-Surface:</u> app. 0,3 kg/m <sup>2</sup>
<b>Fire resistance</b>	A1
<b>Vapour diffusion resistance</b>	$\mu = 10$
<b>Flexural- and tensile bond strength</b>	According to EN 13963
<b>Package-size</b>	5 kg / 25 kg
<b>Storage</b>	Shelf life: Ensure stock rotation and use within 12 months of the marked date. Use unsealed bags within 3 months. Protect from freezing - store between +2°C and +30°C.

For further information please contact:

Saint-Gobain Rigips Austria GesmbH  
Wiener Neustädter Straße 63  
A-2734 Puchberg / Schneeberg

Tel. +43 (0) 2636 / 2203-0  
Fax +43 (0) 2636 / 2206-625

[www.rigips.com](http://www.rigips.com)

Indoor



Application

Manual



Handling

min. 40 min



Working time

app.0,3 kg/m<sup>2</sup>



Consumption

Q1-Q2



Quality standard

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.