

webertherm prestige G

Grey adhesive for all types of thermal insulation

■ /pDescription

- **webertherm prestige G** is a high quality adhesive, made of grey cement, qualitative fillers and additives, and enriched with suitable polymers.

■ Advantages

- Easily prepared and applied
- For the adhesion and reinforcement layer on all insulation boards (**EPS/XPS/stone wool, EPS Graffiti**)
- Produced from high-quality raw materials that make it possible to use it in thicker layers and on low-adhesion insulating slabs.

■ Scope of use

- **webertherm prestige G** is used for installing and reinforcing all thermal insulation materials (EPS, XPS, rock wool, etc.) to all surfaces (critical surfaces, wood, metal, etc.)
- It is used in thermal insulation systems
- It is also used for flattening surfaces to which thermal insulation systems are installed

■ Surface preparation

- The substrate where the thermal insulation panels will be applied must be strong, stable, clean and free of dust or microorganisms.
- Possible problems with the substrate should be repaired before starting the work.
- The work surface should be protected with scaffolding mesh from direct impact of wind, sun or rain, it is advised not to work under severe weather conditions.
- The air and substrate temperature during application and drying should be above 5°C and below 30°C

■ Application

- The 25kg bag content is mixed with an electric mixer by gradually adding 6.5-7 l of water as needed.
- After the first mix, the mass is left at rest for about 10 min and then mixed again before applying, the prepared mass should be used within 3 hours.
- If the adhesive is to be applied to EPS, XPS, or relatively lightweight insulation materials, it should be applied backwards, in the frame, and 3 large measurements between insulating tiles.
- If the adhesive is to be used for thermal insulation with stone wool tiles, it should be applied to the entire surface of the 10x10 serrated scaffold in the case of flattened surfaces.
- Installation of grooves and reinforcement mesh is possible 2 days after the adhesive bonding.
- The surface of the insulation panels is leveled with a layer of 2-4 mm thick layer on which the netting is made, in 1/3 of the thickness of the adhesive layer, the grinding layer must be made after the previous layer has completely dried.
- The decorative finishing layer should be applied at least 7 days after application of the last layer of adhesive.
- For buildings with a height of more than 3m, it is advisable to use the façade ups for fixing the panels to the plinth, 6 anchors / m²
- The adhesive is not recommended to be used for filling residual spaces between thermal insulation tiles - should be filled with insulating material.

■ Tools

- For mixing: electric mixer
- For application: steel trowel

webertherm prestige G

Grey adhesive for all types of thermal insulation

■ Expiration

12 months stored on pallets in a dry place with no direct impact of weather conditions and moisture. Protect from freezing.

webertherm prestige G

Grey adhesive for all types of thermal insulation

Technical Data Table

Packing	Papper bag
Quantity per unit	25 kg / bag
	1400 kg / pallet
Color	white
Granulation	0.7 mm
Consumption	8-10 kg/m ²
Consumption (adhesion)	6-7 kg/m ²
Consumption (reinforcement)	2-3 kg/m ²
Water consumption	8.25 l
Layer thickness	3 mm

The data on consumption are orientative and depending on the characteristics of the base and the application technique.



*Shenim: Te gjitha keto parametra jane te lidhura me kushtet standarde te motit, temperatures 20°C dhe lagështisë relative deri ne 65%. Ne qofte se kushtet e motit nuk jane ne perputhje me proceduren e mesiperme eshte e nevojshme qe te punohet per te pershtatur rrethanat. Weber garanton se cilësia e produkteve te dorëzuar perputhet me te gjitha normat dhe rregullat e prodhimit. Kompania nuk eshte pergjegjese per gabime ne aplikimin e ketij materiali, per perdorimin e materialit per qellime jo te rekomanduara ne pershkrimin e produktit, si dhe per aplikimin ne kushte te tilla atmosferike qe nuk jane ne perputhje me specifikat ne pershkrimin e produktit. Weber rekomandon qe perpara fillimit te punes, te behet nje test sipërfaqeje. Kompania pranon ankesa vetem ne cilesine e produktit qe mund te ketë qene ruajtur, pergatitur dhe aplikuar sipas udhezimeve te leshuara.



SAINT-GOBAIN CONSTRUCTION PRODUCTS ALBANIA sh.p.k

Rr. Budull, Nr.3 • 1039 Ahmetaq

Vore • Shqiperi

www.saint-gobain.com

NIPT : L61822023H