

CERTIFICATE OF CONSTANCY OF PERFORMANCE

No. 0751-CPR-223.5-01

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

Mineral wool products

Thermal insulation products for buildings

Factory made mineral wool (MW) products acc. EN 13162:2012+A1:2015

(details see annex)
produced by or for

Saint Gobain Hellas ABEE

Kleisouras 5

Metamorfosi 144 52

GREECE

and produced in the manufacturing plant(s)

Plant T, Greece

This certificate attests that all provisions concerning the assessment and verification of Constancy of Performance described in Annex ZA of the standard

EN 13162:2012+A1:2015

under **System 1** for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

Constancy of Performance of the construction product.

This certificate was first issued on 09.06.2016 and will remain valid (but no longer than 18.12.2026) as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Gräfelfing, 28 October 2025



Dr. Andreas Schmeller

Certification Body

ANNEX TO CERTIFICATE OF CONSTANCY OF PERFORMANCE

No. 0751-CPR-223.5-01

Factory: Plant T, Greece

Construction product(s): Factory made mineral wool (MW) products acc. EN 13162:2012+A1:2015

Intended use: Thermal insulation products for buildings

**Level(s) or class(es)
Reaction to fire:** For uses subject to regulations of reaction to fire A1, A2, B, C. Products for which a clearly identifiable stage in the production process results in an improvement in the reaction to fire classification.

System of Assessment and Verification of Constancy of Performance: 1

Table 1: Description of the building products

Note: All products without facings have fire classification A1

No.	Product			Classification		
	Name	Description	Thickness Range Mm	Reaction to fire class	Facing	Classification Reports*
1	Isover Orsik	board	30 - 160	A1	AL, YM, YA	1, 2, 3
				C-s1, d0	AX	4
2	Isover Uni	board	30 - 160	A1	AL, YM, YA	1, 2, 3
				C-s1, d0	AX	4
3	Isover Fassil	board	30 - 160	A1	AL, YM, YA	1, 2, 3
				C-s1, d0	AX	4
4	Isover Maxil	board	30 - 160	A1	AL, YM, YA	1, 2, 3
				C-s1, d0	AX	4
5	Isover N	board	30 - 160	A1	AL, YM, YA	1, 2, 3
				C-s1, d0	AX	4
6	Isover Profi Fassade	board	30 - 300	A1	AL, YM, YA	1, 2, 3
				C-s1, d0	AX	4
7	Isover Fassade	board	50 - 300	A1	AL, YM, YA	1, 2, 3
				C-s1, d0	AX	4

*) All products without facings have fire classification A1

- 1) AL - Aluminium compound foil
- 2) YM - Black glass tissue
- 3) YA - White glass tissue
- 4) AX - Reinforced aluminum craft foil
- 5) unfaced

* Explanations regarding reaction to fire characteristics see page 2.

Explanations regarding reaction to fire characteristics:

- *) All products without facings have fire classification A1 – classification reports MPA Hannover no. 235488 and 241323. Additional classification report MPA Hannover 183964
- 1) AL - Aluminium compound foil - MPA Hannover no. 235484 and 241324, product with 20 mm and 0,9 kg/m² classified A1 at 45 kg/m³; product with 25 mm and 0,9 kg/m² classified A1 at 36 kg/m³. Additional classification report MPA Hannover 153214, classification valid for ≥ 20 mm, 120 kg/m³ - 200kg/m³, moc ≤ 5,7 %
 - 2) YM - Black glass tissue - MPA Hannover no. 235482 and 241284. Additional classification report MPA Hannover 153139, classification valid for ≥ 20 mm, 120 kg/m³ - 200kg/m³, moc ≤ 5,7 %
 - 3) YA - White glass tissue - MPA Hannover no. 235480 and 241052 Additional classification report MPA Hannover 152467, classification valid for ≥ 20 mm, 120 kg/m³ - 200kg/m³, moc ≤ 5,7 %
 - 4) AX - Reinforced aluminum craft foil - MPA Hannover no. 235486 and 241602 Additional classification report MPA Hannover 153219, classification valid for ≥ 20 mm, 120 kg/m³ - 200kg/m³, moc ≤ 5,7 %
 - 5) unfaced - Classification reports MPA Hannover no. 235488 and 241323 Additional classification report MPA Hannover and 183964, classification valid for ≥ 20 mm, 20 kg/m³ - 200kg/m³, moc ≤ 5,7 %

Gräfelfing, 28 October 2025



Dr. Andreas Schmeller

Certification Body

