

Gyproc Aquaroc Screws for External Walls



The Aquaroc screws for external walls are self-drilling screws for Gyproc Aquaroc cement board and in general are for fixing boards on metal frames from 0,8 to 2 mm of thickness. These screws have flat trumpet head with ribs in order to make easier the fixing in the board. The screws have a coating that improves the resistance to oxidation and makes them suitable for installation in wet areas or on external walls. They are supplied in boxes 500 pcs/box. Each box contains an insert.

Technical specifications

Specifications	Value	Unit of Measure	Norm
Screw type	Self tapping		
Head	Flat trumpet		
Thread	Single medium		
Point	Cutting		
Steel type	Carbon steel with a minimum surface hardness of 55 HRC		
Screw coating	Ruspert coating		
Head tipe	Phillips n. 2, minimum depth 3 mm		
Corrosion resistance class	1000		
Reaction to fire	A1		
Fastening speed (metal structure 0.8 mm thick and screwdriver > 2000 gg / min)	<1 second		
Color	Silver		

Technical Data Sheet
**Gyproc Aquaroc Screws for
 External Walls**

Product available

Article code	Product	Length mm	Diametr mm	Pcs / Box
5200585749	Viti Aquaroc da esterno 4,2x25 PT	25	4,2	500
5200585750	Viti Aquaroc da esterno 4,2x40 PT	40	4,2	500

Documents and certificates available

Saint-Gobain Italia S.p.A.

Via G. Bensi, 8 • 20152 Milano
 sg-italia@saint-gobain.com | www.gyproc.it

Registro Imprese: Milano n. 08312170155 • R.E.A.: Milano n. 1212939
 Capitale Sociale: Euro 77.305.082,40 i.v. • Codice Fiscale e P. IVA: 08312170155
 Soggetta ad attività di direzione e coordinamento di Saint-Gobain Produits Pour la Construction S.A.S.

